



TEMPERATURE RATING OF FIELD INSTALLED CONDUCTORS MUST BE AT LEAST 140 DEG. F. (60 DEG. C.). TERMINAL STRIPS AND GROUND LUG USE COPPER CONDUCTORS ONLY.  
 CONNECT GROUND LUG IN PANEL TO A SECURE EARTH GROUND  
 DASHED LINES REPRESENT FIELD WIRING

NOTICE: THIS DRAWING CONTAINS PROPRIETARY INFORMATION AND IT SHALL NOT BE USED OR REPRODUCED BY ITS CONTENTS DISCLOSED IN WHOLE OR IN PART, WITHOUT PRIOR WRITTEN CONSENT.										<b>SJE-Rhombus</b>			
REV	ECO N/L	DATE	DRN	APPD	DRN BY	DATE	CHKD BY	DATE	APPD BY	DATE	PROJECT NO	QUOTE NO.	REV
B	8674	2/17	GDV	GDV	JJ	8/11/15	JJ	8/11/15	ACB	8/11/15	1045041	N/A	B
A	7506	8/15	JJ		DEM NAME		DEM P/N		PAGE	SCALE	TITLE		
					N/A		N/A		1 of 1	NONE	LIT. SCHEM MECH AER W/ETM W/AUX		

# FUJI CLEAN C PANEL WIRING DIAGRAM